



HIP-FRONT D REPLACEMENT KIT FOR TREEMOTION
HÜFT-BEIN-KIT FÜR TREEMOTION
KIT DE CINTURA Y PERNERA PARA TREEMOTION
KIT TAILLE / CUISSES POUR TREEMOTION
KIT CINTURA E COSCIALI PER TREEMOTION
HEUP-BEENKIT VOOR TREEMOTION



Teufelberger®

TOGETHER IN MOTION

ENGLISH

TEUFELBERGER Ges.m.b.H.

Vogelweiderstraße 50, 4600 Wels, Austria

T +43 7242 413-0

F +43 7242 413-169

E fiberrope@teufelberger.com

www.teufelberger.com

CAUTION

This spare part may be replaced only by a duly qualified person or under the supervision of such duly qualified person. In doing so, be sure to follow these User Instructions!

Such replacement can also be performed by the harness manufacturer for a given fee. If you opt for this possibility, please send your harness to the address indicated above! If you are uncertain as to whether you have the necessary knowledge and experience, please be sure to consult with a duly qualified person or with the harness manufacturer.

For such replacement, it is imperative that you use only a spare part approved by the manufacturer and provided together with this Product Information leaflet. It must only be used for the purpose set forth below. Before using the harness again, be sure to verify that the spare part has been replaced correctly. If you lack the experience, skills, and knowledge that are necessary for this job, please consult with a duly qualified person or with the harness manufacturer.

CAUTION

Use of the products can be dangerous. Our products are to be used only for their intended purpose. The customer must ensure that the user is familiar with the proper application and the necessary safety procedures. Be aware that every product can cause harm if it is used improperly or overloaded.

INSTALLATION INSTRUCTIONS

NOTE

We have used a red replacement part in the images below to enhance its' visibility. The equivalent replacement part included in this kit is black.



1. Remove the used connection being careful not to damage any other part of the harness.



2. Thread the replacement webbing part under the red lying ring as shown in the image (the cut end of webbing is facing the harness). Do not pull the stitching beyond the ring.



3. Pass the other end of the webbing part through the loop.



4. Pull the unstitched end of webbing to form a choked bite of webbing around the red lying ring. The cut end of webbing is now facing away from the harness.



5. Thread the end of the webbing through the upper slot of the front hardware. Take care to ensure that the webbing passes from the middle of the harness toward the outer side of the harness.



6. Pass the webbing through loop of elastic material.


INSTALLATION INSTRUCTIONS



7. Ensure that the two adjuster buckle parts are sitting correctly. Pass the webbing through the slot closest to the waist belt.



8. Now pass the webbing over the centre rib of the buckle and thread it through the slot closest to the webbing keeper that holds the two buckle parts together.



Check the buckle assembly for correct function before proceeding. If in doubt, check Section J of the treeMOTION User Instructions.



9. Pass the webbing through loop of elastic material again. Before proceeding, ensure that all parts are in the correct place, are not twisted and that the buckles function correctly.



10. Insert the lower rivet part through the folded up strap and connect it to the upper rivet part it to the upper rivet part.



11. Place the strap on a solid surface, and use a hammer to drive the rivet into place.

Repeat the assembly steps shown in pics 1 to 11 for the second Hip/Leg connection.

When using the harness, please be sure to observe the product information regarding our TreeMOTION product. Any and all information concerning transport, storage, and cleaning also apply to the harness with exchanged Hip/Leg connection.

Please keep in mind that the useful life of the harness will depend on the condition of the entire harness. The Hip/Leg connection is only one of the harness components – replacing it will prolong harness life only if all other components of the harness are in a serviceable condition. To evaluate the condition, please observe treeMOTION User Instructions and/or consult a person competent to make such decisions.

DEUTSCH

TEUFELBERGER Ges.m.b.H.

Vogelweiderstraße 50, 4600 Wels, Austria

T +43 7242 413-0

F +43 7242 413-169

E fiberrope@teufelberger.com

www.teufelberger.com

ACHTUNG

Das Ersatzteil darf nur von einer sachkundigen Person oder unter deren Aufsicht getauscht werden. Beachten Sie dabei diese Gebrauchsanleitung!

Der Austausch kann auch gegen Entgelt vom Gurthersteller durchgeführt werden. Schicken Sie dazu den Gurt an die oben angegebene Adresse! Wenn Sie unsicher sind, ob Sie über das nötige Wissen und die Erfahrung verfügen, konsultieren Sie unbedingt eine sachkundige Person oder den Gurthersteller.

Für den Austausch darf ausschließlich das vom Hersteller zugelassene Ersatzteil verwendet werden, welches dieser Herstellerinformation beiliegt. Es darf nur für den unten beschriebenen Verwendungszweck verwendet werden. Kontrollieren Sie unbedingt vor neuerlichem Gebrauch des Gurtes, ob das Ersatzteil korrekt ausgetauscht worden ist. Sollten Sie dazu nicht über die nötige Erfahrung, Fähigkeiten und Wissen verfügen, konsultieren Sie eine sachkundige Person oder den Gurthersteller.

ACHTUNG

Die Verwendung der Produkte kann gefährlich sein. Unsere Produkte dürfen nur für den Einsatz verwendet werden, für den sie bestimmt sind. Der Kunde muss dafür sorgen, dass die Verwender mit der korrekten Anwendung und den notwendigen Sicherheitsvorkehrungen vertraut sind. Bedenken Sie, dass jedes Produkt Schaden verursachen kann, wenn es falsch verwendet oder überlastet wird.

MONTAGEANLEITUNG

HINWEIS

Das Ersatzteil ist nur zur besseren Erkennung auf den Fotos in der Farbe Rot abgebildet. Das mitgelieferte Gurtband ist schwarz.



1. Entfernen Sie das gebrauchte Gurtband und geben Sie dabei Acht, keine anderen Teile des Gurtes zu beschädigen.



2. Ersatz-Gurtband unter den roten Ring fädeln wie im Foto dargestellt, Schnittkante zum Gurt zeigend. Die Vernähung nicht außerhalb des Ringes ziehen.



3. Gurtband in die Schlaufe fädeln.



4. Gurtband festziehen, die Schnittkante zeigt vom Gurt weg.



5. Fädeln Sie das Ende des Gurtbandes durch den oberen Schlitz des Beschlagteils. Geben Sie Acht, dass das Gurtband von der Mitte zur Außenseite des Gurtes verläuft.



6. Ziehen Sie das Gurtband durch die elastische Schlaufe.


MONTAGEANLEITUNG



7. Fädeln Sie das Gurtband durch den dem Gurt am nächsten liegenden Schlitz.



8. Gurtband durch den anderen Schnallen-Schlitz fädeln.



Vergewissern Sie sich, dass die Schnallen-Schlitz korrekt funktionieren bevor Sie fortfahren. Bei Zweifeln kontrollieren Sie Teil J der TreeMOTION Anleitung.



9. Gurtband wieder durch die elastische Gurtschleufe fädeln. Stellen Sie sicher, dass alle Teile am korrekten Platz positioniert und nicht verdreht sind und die Schnallen korrekt funktionieren.



10. Nietenunterteil durch den zusammengelegten Gurt stecken und mit dem Nietenoberteil verbinden.



11. Gurt auf eine feste Unterlage legen und Nieten mittels eines Hammers zusammenschlagen.

Montageschritte von Bild 1 bis Bild 11 an der zweiten Hüft-Beinverbindung wiederholen.

Bei der Verwendung des Gurtes ist die Herstellerinformation zum TreeMOTION zu beachten. Alle Aussagen zu Transport, Lagerung und Reinigung gelten auch für den Gurt mit ausgewechselter Hüft-Bein-Verbindung.

Bitte beachten Sie, dass die Lebensdauer des Gurtes vom Zustand des gesamten Gurtes abhängt, die Hüft-Bein-Verbindung ist nur ein Bestandteil des Gurtes – ihr Tausch verlängert die Lebensdauer nur dann, wenn alle anderen Bestandteile des Gurtes in guter Verfassung sind. Zur Beurteilung des Zustandes beachten Sie bitte die Herstellerinformation zum TreeMOTION oder kontaktieren Sie eine fachkompetente Person.

