



555RXT

Husqvarna 555RXT is a very powerful brushcutter developed for full time work in tough conditions. The X-Torq® engine provide raw power, rapid acceleration and excellent fuel economy. Long shaft and bevel gear angled 35 degrees simplifies wider sweeps. Very low vibrations thanks to LowVib®. Delivered with Balance XT harness.



GRASS BEVEL GEAR

Bevel gear designed with high torque and the cutting equipment parallel to the ground for best cutting performance



ADJUSTABLE HANDLE BAR

Adjustable and ergonomically designed handlebar for best comfort.



X-TORQ® ENGINE

The X-Torq® engine design reduces harmful exhaust emissions by up to 75% and increases fuel efficiency by up to 20%.



LONG SHAFT

Long shaft providing extended reach, facilitating grass clearing.

Features

- Extra comfort with Balance XT harness
- High handle bar, more leg space
- Fuel pump for easy starting
- Optimised gear angle for best cutting performance
- Smart Start® for easy starting
- Auto return stop switch for easy starting
- Ergonomic designed handles
- Comfortable handles
- Easy switch of cutting equipment
- LowVib® sparing the user's arms and hands
- Adjustable harness hook eyelet
- Comfortable handle design
- Soft grip handles
- Tap 'n Go trimmer head

Technical data

Cylinder displacement	53.3 cm ³ / 3.25 cu.inch
Power output	2.8 kW
Maximum power speed	9000 rpm
Maximum recommended engine speed	12000 rpm
Carburettor	Walbro WT
Fuel tank volume	1.1 lit / 37.2 fl oz
Fuel consumption	480 g/kWh
Idling speed	2800 rpm
Spark plug	NGK BPMR7A
Lubricant type	Husqvarna 2 stroke or equiv. at 50:1
Exhaust emissions (HC average)	61 g/kWh
Exhaust emissions (CO average)	350 g/kWh
Exhaust emissions (NOx average)	2.4 g/kWh
Equivalent vibration level (ahv, eq) left / right handle	1.5/1.6 m/s ²
Sound pressure level at operators ear	101 dB(A)
Sound power level, guaranteed (LWA)	120 dB(A)
Gear ratio	1:1.46
Drive gear angle	35 °
OEM Trimmer head	T55XM12
OEM Grass blade	Multi 350-3
OEM Harness	Balance XT
Weight (excl. cutting equipment)	9.2 kg / 20.44 lbs
Tube length	1483 mm / 58.39 inch
Tube diameter	35 mm / 1.38"

ARTICLES

966 62 90-01	T55X + Multi 350-3 (1"), All ex US50, CAN ,AUS, NZ	£ 1,024.99	£ 1,229.99
--------------	--	------------	------------

